

USB Gen 1 Type-C 8-in-1 MST Dual 4K60Hz Display Travel Dock



Product Name:

USB Gen 1 Type-C 8-in-1 MST Dual 4K60Hz Display Travel Dock

Product Series: Docking

Product Code: CSV-1597

EAN code: 8719214472368

UPC code: 841615102716

Description:

The Club 3D CSV-1597 USB Gen 1 Type-C 8-in-1 MST Dual 4K60Hz Display Travel Dock with HDMI™ 8K30Hz(HDR), DisplayPort™ 8K30Hz, 2x USB Gen 1 Type-A, BC1.2, RJ45, SD/Micro SD card slots and USB Gen 1 Type-C PD3.0 Female port, provides a very advanced, efficient solution to extend a single USB Gen 1 Type-C port to be multiple ports. It integrates video, data and power ports that allows to connect 2 displays simultaneously for enjoying videos on a larger screen, connect multiple USB Gen 1 devices for data transmission up to 5Gbps, connect a Gigabit Ethernet source for getting your PC connected to super high speed network, or connect to headset to enjoy fantastic music. It also provides PD charging for support up to max. 100W PD charging. This is for operating this device and charge the host simultaneously. It can work on all DP™1.4 Alt mode supported USB Gen 1 Type-C hosts.

Features:

- Support DP™1.4 Alt mode max. 8K@30Hz(with DSC1.2)
- Support HDMI™ max. 8K@30Hz(with DSC1.2)
- Support Dual display HDMI™+ DP™ max.4K60Hz (MST with DSC1.2)
- Max 5Gbps data transmission per USB Gen 1 Type-A port
- Support max. 7.5W(5V/1.5A) downstream charging, 2 USB Gen 1 Type-A share max. 1.5A output
- Support Gigabit Ethernet 10M/100M/1000M
- Support SD3.0 UHS-I up to 832Mbps/104MB/s data rate, allow 2 card slots to work simultaneously
- Support PD3.0 with max. 100W PD charging

NOTE: Please make sure your host supports DP™1.4 Alt mode.

Input:

- 1x USB Gen 1 Type-C Male (Connect to host)
Support DP™1.4 Alt mode

Note: To get max. bandwidth, the host should support DP™1.4 Alt mode

Output(s):

- 1x HDMI™
Support max. 8K30Hz
- 1x DisplayPort™
Support max. 8K30Hz
- Support Dual display HDMI™+ DP™ max.4K60Hz (MST with DSC1.2)

Note: The max. resolution of the display determined by the computer and the monitor

- 2x USB Gen 1 Type-A
Max. 5Gbps data transmission per port
Support max. 7.5W(5V/1.5A) downstream charging.
2 USB Gen 1 Type-A ports share max. 1.5A output
Support short-circuit, over-current, over-voltage protection
- 1x RJ45
Support Gigabit Ethernet, 10M/100M/1000M
- 2x SD/Micro SD 3.0
Support UHS-I up to 832Mbps/104MB/s data rate
Allow 2 card slots to work simultaneously
- 1x USB Gen 1 Type-C Female (for PD Charging)
Support max. 100W PD charging
Support PD3.0 Fast Role Swap, the connected device will not get disconnected while plugging in and out the PD

Note:

- Please update your TV Firmware to the version which supports these resolutions/refresh rates!
- Please update your Graphic drivers on your PC and make sure that DSC1.2 is supported on your devices to support the these resolutions/refresh rates!

Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d.com and it will be our pleasure to assist you.



OS Support:

- Microsoft® and Apple®

In the box:

- 1x USB Gen 1 Type-C 8-in-1 MST Dual 4K60Hz Display Travel Dock

Available Interfaces

Input:

- USB Gen 1 Type-C Male
(Connect to host)

Output:

- 1x HDMI™ Female
- 1x DisplayPort™ Female
- 2x USB Gen 1 Type-A Female
- 1x RJ45
- 1x SD / 1x Micro SD 3.0
- 1x USB Gen 1 Type-C Female

Other info:

- Box size: 25 x 8 x 3.5cm / 9.84 x 3.15 x 1.38"
- Cable length: 18 cm / 7.09"
- Total length: ± 31.6 cm / 12.44"
- Hub dimensions: 13 x 4.5 x 1.4 cm / 5.12 x 1.77 x 0.55"
- Connector dimensions: 3.4 x 1.2 x 0.65 cm / 0.86 x 0.47 x 0.26"
- Product Weight: 82 gr / 4.13 oz
- Box Weight: 54 gr / 1.9 oz
- Total Weight: 136 gr / 4.79 oz
- Meets ROHS, FCC, and CE EMI requirements

Input:



Output:

